



# PRO-GUARD

## Grease Cartridge Range



Pro-Guard from Rock Oil is a premium quality range of lubricating greases, formulated with extreme additives and mineral base oils, capable of a multitude of industrial, automotive, agricultural, and construction applications. Suitable for grease guns (with an SR screw fit), the Pro-Guard 400g and 500g range allows for accurate and clean lubrication of machinery with an achievable pressure of 400 bar.

**PRO-GUARD**  
TAC EP 2\*

PN. 67050 | 500g

A premium quality, super-tacky high performance, Lithium thickened NLGI No2 lubricating grease, formulated with extreme additives and mineral base oil for high load applications. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



BLUE, SUPER TACKY, NLGI-2 LITHIUM  
180 BASE OIL  
Operating Temperature Range: -20°C to +140°

**PRO-GUARD**  
LCR EP 2\*

PN. 65102 | 500g

A premium quality, high temperature, Lithium Complex thickened NLGI No2 lubricating grease, formulated with mineral base oil. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



RED, NLGI-2 LITHIUM COMPLEX  
150 BASE OIL  
Operating Temperature Range: -20°C to +150°

**PRO-GUARD**  
MO EP 2\*

PN. 65103 | 500g

A premium quality, Lithium thickened NLGI No2 lubricating grease, formulated with mineral base oil and fortified with Molybdenum Disulphide (MoS2) for high load applications. Contains extreme pressure and oxidation resistant additives designed to reduce wear, improve grease performance and extend component life.



MOLY LITHIUM  
180 BASE OIL  
Operating Temperature Range: -20°C to +140°

**PRO-GUARD**  
EP 2\*

PN. 65123 | 500g

A premium quality, Lithium thickened NLGI No2 lubricating grease, formulated with extreme additives and mineral base oil. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



NLGI-2 LITHIUM  
180 BASE OIL  
Operating Temperature Range: -20°C to +140°

**PRO-GUARD**  
LC 460 EP2

PN. 64200 | 400g

A premium quality, super heavy duty, Lithium Complex thickened NLGI No2 lubricating grease, formulated with mineral base oil. Contains extreme pressure and oxidation resistant additives designed to reduce wear, improve grease performance and extend component life.



YELLOW, NLGI-2 LITHIUM COMPLEX  
460 BASE OIL  
Operating Temperature Range: -20°C to +150°

\* Pro-Guard TAC EP2, LCR EP 2, MO EP 2, AND EP 2 also available in 400g cartridge.

### HEAD OFFICE

- ✓ MALONE HOUSE, 90 PRIESTLEY STREET  
WARRINGTON, CHESHIRE, WA5 1ST
- @ SALES@ROCKOIL.CO.UK
- ☎ +44 (0) 1925 636191

### SOUTHERN OFFICE

- ✓ UNIT 17, DUNKIRK BUSINESS PARK  
FROME ROAD, SOUTHWICK, TROWBRIDGE  
WILTSHIRE, BA14 9NL
- ☎ +44 (0) 1225 719000

### WEB/SOCIAL

- 🌐 ROCKOIL.CO.UK
- f ROCKOIL.LUBRICANTS
- 🐦 ROCKOILNEWS
- 📷 ROCKOILNEWS