



KOOL-GUARD

Coolant Range



The Rock Oil Kool-Guard range has been specifically engineered to offer the ultimate protection, whatever your application or industry. They serve the agricultural, automotive, commercial, construction, industrial, marine and plant sectors. Coolants have to work harder than ever before to ensure optimum performance and reliability and by using Kool-Guard you can be sure you are offering the very best coolant solution for your equipment.

<p>KOOL-GUARD MEG UK</p>  <p>MEG BASED COOLANT CONCENTRATE</p> <p>AFNOR NF R15-601 • AS 2108 • ASTM D3306 • BS 6580 (2010) • BTC Classification Type 2E • CUNA NC 956-16 • FVV Heft R443 • ONORM V 5123 • SAE J1034 • UNE 26-361</p> <p>ALSO AVAILABLE IN 50:50 READY TO USE PREMIX: KOOL-GUARD MEG - 38</p>	<p>KOOL-GUARD XL UK</p>  <p>MEG BASED OAT COOLANT CONCENTRATE</p> <p>ASTM D3306, ASTM D4985 • BS 6580 (2010) • FORD WSS-M97B44-D • MAN 324 SNF • MB 325.3 • VAG TL 774D/F (G12/G12+) • RENAULT 41-01-001-D • VOLVO VCS (except colour) • GM 1899M, US 6277M, OPEL GM QL130100</p> <p>ALSO AVAILABLE IN 50:50 READY TO USE PREMIX: KOOL-GUARD XL - 38</p>	<p>KOOL-GUARD VCS</p>  <p>MEG BASED OAT COOLANT CONCENTRATE</p> <p>ASTM D3306 • ASTM D 4985 • SAE J 1034 • BS 6580 (2010) • VOLVO VCS</p> <p>ALSO AVAILABLE IN 50:50 READY TO USE PREMIX: KOOL-GUARD VCS - 38</p>	<p>KOOL-GUARD H-OAT</p>  <p>MEG BASED HYBRID HEAVY DUTY COOLANT CONCENTRATE</p> <p>HD4X • G05 • ASTM D3306 • ASTM D 4985 • ASTM D 6210 • SAE J 1034 • BS 6580 (1992) • BRITISH RAIL BR637* • CUMMINS CES14603 • JCB STD00088 (HD) • JOHN DEERE JDM H24 • MAN 324 • PERKINS</p>
<p>KOOL-GUARD HYBRID NF</p>  <p>MEG BASED NAP-FREE HYBRID COOLANT CONCENTRATE</p> <p>AFNOR NF R15-601 • ASTM D3306 • BS 6580:2010 • MAN 3324-NF • MB 325.0 • MTU MTL 5048 • CUMMINS 85T8-2 • Porsche TL-774 C (G 11) • DEUTZ DQC CA-14 • FORD ESD-M97B49-A • JI CASE JIC-501 • FIAT 9.55523 • BMW / MINI GS 94000 • VOLVO CARS • 128 6083 / 002</p> <p>ALSO AVAILABLE IN 50:50 READY TO USE PREMIX: KOOL-GUARD HYBRID NF - 38</p>	<p>KOOL-GUARD ELC</p>  <p>NITRATED OAT ETHYLENE GLYCOL-BASED COOLANT CONCENTRATE</p> <p>OAIT • CAT EC-1 • ASTM D6210 • BS6580:2010</p> <p>ALSO AVAILABLE IN 50:50 READY TO USE PREMIX: KOOL-GUARD ELC - 38</p>	<p>KOOL-GUARD SI-OAT</p>  <p>MEG BASED SILICATED OAT COOLANT CONCENTRATE</p> <p>AS 2108-2004 • ASTM D 3306, D 4985, D 6210 • SAE J1034 • ONORM V 5123 • CUNA NC 956-16 • JIS K 2234:2006 • SANS 1251:2005 • SH 0521-1999 • BS 6580:2010 • VW / Audi / Seat / Skoda / TL 774-G • Lamborghini / Bentley • Daimler/Mercedes-Benz MB 325.5 • MAN MAN 324 Type SI-OAT • Porsche From MY 1996</p>	<p>KOOL-GUARD MPG OAT</p>  <p>MPG OAT COOLANT CONCENTRATE</p> <p>PXLCs - NONE TOXIC - ASTM D3306 TYPE II • BS 6580 (2010) AND AFNOR NF R15-601 •</p> <p>DILUTION: 33:67 -15 °C / 50:50 -32°C / 60:30 -57°C.</p>



✓ MALONE HOUSE, 90 PRIESTLEY STREET, WARRINGTON, CHESHIRE, WA5 1ST, UNITED KINGDOM

☎ +44 (0) 1925 636191

@ SALES@ROCKOIL.CO.UK

🌐 ROCKOIL.CO.UK

f @ROCKOIL.LUBRICANTS

X @ROCKOILNEWS

📷 @ROCKOILNEWS

