



MARINE

Lubricant Range



NMMA approved lubricants - complete marine protection and performance.

At Rock Oil, we utilise our extensive expertise in 2-stroke and 4-stroke lubricants to produce an exceptional range of marine lubricants suitable for both inboard and outboard applications. Among this diverse array of top-tier lubricants, we are particularly proud to have achieved the esteemed NMMA certification for our leading marine lubricants, MP3 Ultra and MP+ Sport, reflecting the exceptional standards we consistently uphold across our product range.

We proudly offer a broad spectrum of marine lubricants formulated to meet specific performance and application needs. Every product in our range reflects our commitment to quality and performance, ensuring a suitable solution for every customer's requirements.

OUTBOARD MARINE ENGINE OIL

| PRODUCT NAME | DESCRIPTION | SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS |
|-----------------------------|---|---|
| MP3 ULTRA | 2-stroke, advanced synthetic, DFI | NMMA TC-W3® (NO. RL 92402B) |
| MP PLUS SPORT 10W-40 | 4-stroke, synthetic, SAE 10W-40 | API SM • NMMA FC-W CC (NO. FC13799W), NMMA FC-W |
| MP PLUS SPORT 5W-30 | 4-stroke, advanced synthetic, SAE 5W-30 | NMMA FC-W(CC)® |
| MP3 SPORT | 2-stroke, semi-synthetic, DFI / non-DFI | NMMA TC-W3® |
| BIO MARINE 3 | 2-stroke, ester-based, biodegradable, non-toxic | NMMA TC-W3® |



INBOARD MARINE ENGINE OIL

| PRODUCT NAME | DESCRIPTION | SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS |
|---------------------|---|--|
| MP4 SPORT | 4-stroke, synthetic, SAE 15W-40 | API CK-4, CJ-4, CI-4 • ACEA E7, E11 • CATERPILLAR ECF-3, ECF-2 & ECF-1A • CUMMINS 20086 • DETROIT DIESEL 93K222 • DEUTZ DQC-III-18-LA, DQC-III-10-LA • MACK EO-S 4.5 • MAN M3775, M3575 • MERCEDES-BENZ /DAIMLER TRUCK 228.31 (DTFR 15C100) • MTU TYPE 2.1 • RENAULT RVI RLD-4, RLD-3 • VOLVO VDS-4.5 • FORD WSS M2C171 F1 |
| MP LITE-D | 4-stroke multi-grade diesel, SAE 15W-40 | API SF/CC |
| MPR INJECTOR | 2-stroke, advanced synthetic, non TC-W3® injector/pre-mix | JASO FD & FC • ISO L-EGD • API TC • ROTAX 253 • HUSQVARNA 346 & 372 MPR INJECTOR MEETS THE REQUIREMENTS OF SEA-DOO JET SKIS AND OTHER ROTAX ENGINED MARINE EQUIPMENT. |



MARINE

Lubricant Range



HEAVY-DUTY MARINE ENGINE OIL

| PRODUCT NAME | DESCRIPTION | SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS |
|-----------------------------|---|--|
| MARINE-GUARD 3015 TP | Medium alkalinity for medium & high-speed trunk piston diesel engines | API CF • SAE 30 • TBN 15 |

| | | |
|-----------------------------|---|--------------------------|
| MARINE-GUARD 4015 TP | Medium alkalinity for medium & high-speed trunk piston diesel engines | API CF • SAE 40 • TBN 15 |
|-----------------------------|---|--------------------------|

ANCILLARY MARINE PRODUCTS

| PRODUCT NAME | DESCRIPTION | SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS |
|-------------------|-------------------------------------|--|
| MARINE PSF | Power steering & transmission fluid | GM DEXRON II |

| | | |
|-------------------|--------------------------|------------------|
| MARINE HSF | Hydraulic steering fluid | DIN 51524 PART 2 |
|-------------------|--------------------------|------------------|

| | | |
|--------------------|--|----------|
| MP GEAR OIL | Extreme-pressure gear oil (Blue/Green), SAE 80W-90 | API GL-5 |
|--------------------|--|----------|

| | | |
|-------------------------------|--|---|
| SUPER MARINE INHIBITOR | | LIGHT MINERAL OIL BLENDED WITH SOPHISTICATED CORROSION INHIBITORS AND OXIDATION STABILISERS |
|-------------------------------|--|---|

SPECIALIST MARINE GREASE

| PRODUCT NAME | DESCRIPTION | SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS |
|------------------------------------|--|--|
| MPG UNIVERSAL MARINE GREASE | Premium quality anhydrous calcium grease | NLGI-3 • WHITE • ANHYDROUS CALCIUM • -20°C TO +120°C |

| | | |
|-----------------------------|--|-----------------------------------|
| MG STERN TUBE GREASE | Premium quality water resistant calcium grease | WHITE • CALCIUM • -20°C TO +110°C |
|-----------------------------|--|-----------------------------------|

| | | |
|---------------------------------|--------------------------|--|
| WATER RESISTANT 2 GREASE | Aluminium complex grease | NLGI-2 • BROWN • ALUMINUM COMPLEX • -20°C TO +140° |
|---------------------------------|--------------------------|--|

| | | |
|---------------------------|---------------------------------------|--------------------------------------|
| HD ADHESIVE GREASE | Semi-synthetic water resistant grease | GREEN • 1000 BASE OIL • -7°C TO +140 |
|---------------------------|---------------------------------------|--------------------------------------|

| | | |
|-------------------------------|--|-----------------------------------|
| PRO-GUARD CA 2Z GREASE | Premium quality water resistant calcium grease | WHITE • CALCIUM • -20°C TO +110°C |
|-------------------------------|--|-----------------------------------|



MARINE

Lubricant Range



ANTI-FREEZE / COOLANTS

| | | |
|------------------------------------|--|---|
| KOOL-GUARD MARINE MPG | Mono Propylene Glycol (MPG), Marine | ASTM D3306 TYPE II • BS 6580 (2010) • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY) |
| KOOL-GUARD MEG -38 | Mono Ethylene Glycol (MEG), Blue | DILUTION 50:50 AFNOR NF R15-601 • AS 2108 • ASTM D3306 • BS 6580 (2010) • BTC CLASSIFICATION TYPE 2E • CUNA NC 956-16 • FVV HEFT R443 • ONORM V 5123 • SAE J1034 • UNE 26-361 |
| KOOL-GUARD XL -38 | Mono Ethylene Glycol (MEG), OAT | DILUTION 50:50 ASTM D3306 • ASTM D4985 • BS 6580 (2010) • DAF 74002 • SAE J1034 • FFV HEFT R443 • CUNA NC 956-16 • UNE 26361-88 • JIS K2234 • NATO S759 • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY) • CHRYSLER MS 9176 • CUMMINS CES 14603 • FORD ESE M97B49-A, WSS-M97B44-D & ESD M97B49-A • GM 1899M, US 6277M, OPEL GM QL130100 • JOHN DEERE H24 B1 & C1 • LEYLAND TRUCKS LTS 22 AF 10 • MACK 014GS 17004 • MAN 248, 324 (SNF), & B&W D 36 5600 • MERCEDES/DAIMLER TRUCK MB 325.3 (DTFR 29C110) • RENAULT 41-01-001-D • VAG TL 774D/F (G12/G12+) • VOLVO VCS (EXCEPT COLOUR) |
| KOOL-GUARD VCS 50:50 PREMIX | Mono Ethylene Glycol (MEG), OAT | DILUTION 50:50 ASTM D3306 • ASTM D4985 • BS 6580 (2010) • SAE J1034 • FFV HEFT R443 • CUNA NC 956-16 • UNE 26361-88 • JIS K2234 • NATO S759 • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY) • CHRYSLER MS 9176 • CUMMINS CES 14603 • FORD ESE M97B49-A, WSS-M97B44-D & ESD M97B49-A • GM 1899M, US 6277M, OPEL GM QL130100 • JOHN DEERE H24 B1 & C1 • LEYLAND TRUCKS LTS 22 AF 10 • MACK 014GS 17004 • MAN 248, 324 (SNF), & B&W D 36 5600 • MERCEDES/DAIMLER TRUCK MB 325.3 (DTFR 29C110) • RENAULT 41-01-001-D • VAG TL 774D/F (G12/G12+) • VOLVO VCS |
| KOOL-GUARD PSi-OAT -38 | Mono Ethylene Glycol (MEG), Sillicated OAT | DILUTION 50:50 AS 2108-2004 • ASTM D 3306, D 4985, D 6210, D7583 • PN-C 4007:2000 • SAE J1034 • ÖNORM V 5123 • CUNA NC 956-16 • JIS K 2234:2206 • CHINA GB 29743-2013 • SANS 1251:2005 • BS 6580:2010 • VOLVO VCS-2 • DEUTZ, DQC CC-14 • DEUTZ-FAHR >04/2017 • HUERLIMANN >04/2017 • LAMBORGHINI-TRACTORS >04/2017 • MAN DIESEL & TURBO >04/2017 • SAME >04/2017 • VOLVO CARS TR-31854114-002 • JOHN DEERE >2011 • PERKINS |

Depending on the range, Rock Oil products are available in multiple sizes, including 400ml aerosols and 1L / 4L / 5L / 20L / 210L / bulk containers.

All products and information are correct at the time of publication. The company reserves the right to change formulations and specifications without prior notice.

For more detailed information on any product and confirmation of the latest specifications please contact us. Full product data sheets and health and safety information is available on request.

Contact sales@rockoil.co.uk for order information and expert advice.



✉ Malone House, 90 Priestley Street, Warrington, Cheshire, WA5 1ST

☎ +44 (0) 1925 636191

rockoil.co.uk