



PRO-GUARD

Grease Cartridge Range



Pro-Guard from Rock Oil is a premium quality range of lubricating greases, formulated with extreme additives and mineral base oils, capable of a multitude of industrial, automotive, agricultural, and construction applications. Suitable for grease guns (with an SR screw fit), the Pro-Guard 400g and 500g range allows for accurate and clean lubrication of machinery with an achievable pressure of 400 bar.

PRO-GUARD
TAC EP 2*
PN. 67050 | 500g

A premium quality, super-tacky high performance, Lithium thickened NLGI No2 lubricating grease, formulated with extreme additives and mineral base oil for high load applications. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



BLUE, SUPER TACKY, NLGI-2 LITHIUM
180 BASE OIL
Operating Temperature Range: -20°C to +140°

PRO-GUARD
LCR EP 2*
PN. 65102 | 500g

A premium quality, high temperature, Lithium Complex thickened NLGI No2 lubricating grease, formulated with mineral base oil. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



RED, NLGI-2 LITHIUM COMPLEX
150 BASE OIL
Operating Temperature Range: -20°C to +150°

PRO-GUARD
MO EP 2*
PN. 65103 | 500g

A premium quality, Lithium thickened NLGI No2 lubricating grease, formulated with mineral base oil and fortified with Molybdenum Disulphide (MoS2) for high load applications. Contains extreme pressure and oxidation resistant additives designed to reduce wear, improve grease performance and extend component life.



MOLYLITHIUM
180 BASE OIL
Operating Temperature Range: -20°C to +140°

PRO-GUARD
EP 2*
PN. 65123 | 500g

A premium quality, Lithium thickened NLGI No2 lubricating grease, formulated with extreme additives and mineral base oil. Suitable for a multitude of industrial, automotive, agriculture, and construction applications.



NLGI-2 LITHIUM
180 BASE OIL
Operating Temperature Range: -20°C to +140°

PRO-GUARD
LC 460 EP2
PN. 64200 | 400g

A premium quality, super heavy duty, Lithium Complex thickened NLGI No2 lubricating grease, formulated with mineral base oil. Contains extreme pressure and oxidation resistant additives designed to reduce wear, improve grease performance and extend component life.



YELLOW, NLGI-2 LITHIUM COMPLEX
460 BASE OIL
Operating Temperature Range: -20°C to +150°

* Pro-Guard TAC EP2, LCR EP 2, MO EP 2, AND EP 2 also available in 400g cartridge.



✓ MALONE HOUSE, 90 PRIESTLEY STREET, WARRINGTON, CHESHIRE, WA5 1ST, UNITED KINGDOM

☎ +44 (0) 1925 636191

@ SALES@ROCKOIL.CO.UK

🌐 ROCKOIL.CO.UK

f @ROCKOIL.LUBRICANTS

X @ROCKOILNEWS

📷 @ROCKOILNEWS

