



# AIR-GUARD

## Compressor Lubricant Range



### AIR-GUARD - The complete solution for compressor lubrication.

The Rock Oil AIR-GUARD range of compressor lubricants are designed to meet the demanding requirements of modern compressor applications. These premium lubricants offer exceptional anti-oxidation and corrosion protection, ensuring extended service life and reliable performance.

AIR-GUARD lubricants are not only ideal for compressors but also versatile enough for various machinery applications requiring superior anti-wear properties and resistance to degradation, including high-speed gears, bearings, pumps, and blowers. This range supports lubricant rationalisation, making it an ideal choice for maintaining optimal efficiency and protection across diverse industrial systems.

#### 2000 HR MINERAL

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> 2000 VG32	2000 HOURS • SCREW	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 2000 VG46	2000 HOURS • VANE / SCREW	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 2000 VG68	2000 HOURS • VANE / PISTON	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 2000 VG100	2000 HOURS • PISTON	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 2000 VG150	2000 HOURS • HYDROVANE	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)

#### 5000 HR SEMI-SYN

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> 5000 VG32	5000 HOURS •	DIN 51 506 VDL, 51 524 PART.2 • VICKERS I-286-S • CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 5000 VG46	5000 HOURS • VANE / SCREW	DIN 51 506 VDL, 51 524 PART.2 • VICKERS I-286-S • CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)

#### 8000 HR ULTRA SYN PAO

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> 8000 VG32	8000 HOURS • SCREW	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 8000 VG46	8000 HOURS • VANE / SCREW	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 8000 VG68	8000 HOURS • VANE / PISTON	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 8000 VG100	8000 HOURS • PISTON	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)
<b>AIR-GUARD</b> 8000 VG150	8000 HOURS • HYDROVANE	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)



# AIR-GUARD




## Compressor Lubricant Range




### 8000 HR ULTRA SYN PAO (CONT.)

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> 8000 VG220	8000 HOURS • HYDROVANE	DIN 51 506 VDL SPERRY VICKERS I-286-S • DIN 51 524 PART.2 CINCINNATI MILACRON P-68, P-69, P-70 • AFNOR NF E 48-603 (HM)

### ULTRA SYN PAO FOOD GRADE

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> FG 68	VANE / PISTON	. 
<b>AIR-GUARD</b> FG 68	VANE / PISTON	. 
<b>AIR-GUARD</b> FG 100	PISTON	. 

### MISC

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
<b>AIR-GUARD</b> ROCKFROST	ANTIFREEZE AIRLINE OIL	. 
<b>AIR-GUARD</b> AIRLINE OIL VG22	AIRLINE OIL ISO 22	.
<b>AIR-GUARD</b> AIRLINE OIL FG VG32	FOOD GRADE AIRLINE OIL ISO 32	.

Depending on the range, Rock Oil products are available in multiple sizes, including 400ml aerosols and 1L / 4L / 5L / 20L / 210L / bulk containers.

All products and information are correct at the time of publication. The company reserves the right to change formulations and specifications without prior notice. For more detailed information on any product and confirmation of the latest specifications please contact us. Full product data sheets and health and safety information is available on request.

Contact [sales@rockoil.co.uk](mailto:sales@rockoil.co.uk) for order information and expert advice.

✉ Malone House, 90 Priestley Street, Warrington, Cheshire, WA5 1ST

☎ +44 (0) 1925 636191



[rockoil.co.uk](http://rockoil.co.uk)